

Upholstery Classification & Test Performance

	Fiber Content	Abrasion Resistance (Martindale) EN ISO 12947-2: 1999+	Pilling/Surface Fuzzing	Colour Fastness to Light	Colour Fastness to Rubbing	
					Wet	Dry
Faux leather	60% Polyester 40% PU	+100,000 cycles	N/A	5	4	3-4
Bouclé fabric	96% Polyester 4% Linnen	+50,000 cycles	3-4	5	4-5	4-5
Urban fabric	96% Polyester 4% Linnen	+100,000 cycles	4-5	4-5	5	5
Nordic fabric	100% Polyester	+100,000 cycles	4-5	4	4-5	4-5
Element fabric	100% Recycled Polyester	+100,000 cycles	4	4-5	4-5	4-5
Vintage artificial leather	PU & Polyester	+25,000 cycles	N/A	4-5	4-5	4-5
RPES bouclé	100% rPES (Recycled polyester)	+90,000 cycles	3-4	5	4-5	5
Velvet	100% Polyester	+50,000 cycles	4	5	4-5	4-5
Soft weave fabric	100% Polyester	+50,000 cycles	4	5	4-5	4-5
The scale goes from 1-5, where 5 is the highest score (no changes to the material) and 1 is the lowest.						